

(12) United States Patent

Hayton et al.

(56)

(10) **Patent No.:**

(45) Date of Patent:

US 9.183.810 B2

Nov. 10, 2015

(54) ELECTRONIC DOCUMENT READING **DEVICES**

Applicant: FLEXENABLE LIMITED,

Cambridgeshire (GB)

Inventors: Carl Hayton, Cambridge (GB); Victor

T. Pan, Fremont, CA (US); Kenneth R.

Venegas, San Jose, CA (US)

Assignee: FLEXENABLE LIMITED, Cambridge

(GB)

Notice:

Subject to any disclaimer, the term of this patent is extended or adjusted under 35

U.S.C. 154(b) by 38 days.

Appl. No.: 14/088,646

Filed: Nov. 25, 2013 (22)

(65)**Prior Publication Data**

US 2014/0071078 A1 Mar. 13, 2014

Related U.S. Application Data

(62) Division of application No. 12/647,632, filed on Dec. 28, 2009, now Pat. No. 8,619,021.

(30)Foreign Application Priority Data

Oct. 23, 2009 (GB) 0918619.8

Int. Cl.

G09G 3/34 (2006.01)G09G 5/00 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC G09G 5/003 (2013.01); G06F 1/1626 (2013.01); G06F 1/1643 (2013.01); G06F 1/1652 (2013.01); G06F 3/044 (2013.01); G06F 3/0412 (2013.01); G09G 3/344 (2013.01)

Field of Classification Search

CPC G09G 5/003; G06F 1/1626; G06F 1/1643; G06F 1/1652; G06F 3/01412; G06F 3/044; G06F 3/344

See application file for complete search history.

References Cited

U.S. PATENT DOCUMENTS

6,021,306 A 2/2000 McTaggart 9/2000 Jacobson 6,124,851 A

(Continued)

FOREIGN PATENT DOCUMENTS

8/2006 GB 2446499 JP 2001356323 12/2001

(Continued)

OTHER PUBLICATIONS

United Kigdom Search Report for corresponding Application No. GB0918619.6 dated Feb. 22, 2010.

(Continued)

Primary Examiner — Jonathan Boyd (74) Attorney, Agent, or Firm — Snell & Wilmer L.L.P.

(57)ABSTRACT

We describe an architecture for a large-area, touch-sensitive electronic document reading device which is able to tolerate bending. In broad terms, a control circuit board is mounted behind a flexible display structure in the housing and at respective points of attachment of first and second laminar connectors to the control circuit board each laminar connector has a plurality of electrical connections running along a longitudinal direction of the laminar connector and disposed alongside one another in a transverse direction across the laminar connector. At the respective points of attachment of the first and second laminar connectors to the control circuit board the longitudinal directions of the laminar connectors are aligned such that, when said device is flexed, a relative displacement in said longitudinal direction between said control circuit board and of said display structure can be tolerated without damage to the control electronics, touch sensitive display screen or connections therebetween.

6 Claims, 14 Drawing Sheets

